



10PS26

LF Drivers - 10.0 Inches

700 W continuous program power capacity
76 mm (3 in) aluminium voice coil
55 - 4000 Hz response
96 dB sensitivity
Shorting copper cap for extended HF response



Specifications

Nominal diameter	250 mm (10.0 in)
Nominal impedance	8 Ω
Minimum impedance	7.1 Ω
Nominal power handling ¹	350 W
Continuous power handling ²	700 W
Sensitivity (1W/1m) ³	96.0 dB
Frequency range	55 - 4000 Hz
Voice coil diameter	76 mm (3.0 in)
Winding material	Aluminium
Former material	Glass Fibre
Winding depth	18 mm (0.71 in)
Magnetic gap depth	10 mm (0.4 in)
Flux density	0.9 T

Design

Surround shape	Double Roll
Cone shape	Exponential
Magnet material	Ferrite

Design

Spider	Single
Pole design	T-Pole
Recommended enclosure	25.0 dm ³ (0.88 ft ³)
Recommended tuning	65 Hz

Parameters⁴

Fs	54 Hz
Re	6.0 Ω
Qes	0.33
Qms	2.9
Qts	0.29
Vas	38.0 dm ³ (1.3 ft ³)
Sd	320.0 cm ² (49.1 in ²)
η_0	1.8 %
Xmax	5.5 mm
Xvar	5.0 mm
Mms	33 g
Bl	14.1 Txm
Le	1.2 mH

Parameters

EBP	163 Hz
-----	--------

Mounting And Shipping Info

Overall diameter	262 mm (10.3 in)
Bolt circle diameter	245 mm (9.6 in)
Baffle cutout diameter	230.0 mm (8.8 in)
Depth	123 mm (4.8 in)
Flange and gasket thickness	14 mm (0.55 in)
Air volume occupied by driver	0.0 dm ³ (0.0 ft ³)
Net weight	6.0 kg (13.2 lb)
Shipping weight	6.7 kg (14.7 lb)
Shipping box	320x320x160 mm (12x12x6.3 in)

Service Kit

RCK010PS268

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.
2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.