

15PLB76

LF Drivers - 15.0 Inches

800 W continuous program power capacity
76 mm (3 in) copper voice coil
40 - 2000 Hz response
100 dB sensitivity



Specifications

Nominal diameter	380 mm (15.0 in)
Nominal impedance	8 Ω
Minimum impedance	6.2 Ω
Nominal power handling ¹	400 W
Continuous power handling ²	800 W
Sensitivity (1W/1m) ³	100.0 dB
Frequency range	40 - 2000 Hz
Voice coil diameter	76 mm (3.0 in)
Winding material	Copper
Former material	Glass Fibre
Winding depth	16 mm (0.62 in)
Magnetic gap depth	11 mm (0.4 in)
Flux density	1.15 T

Design

Surround shape	Triple Roll
Cone shape	Exponential
Magnet material	Ferrite

Design

Spider	Single
Pole design	T-Pole
Woofer cone treatment	WP Waterproof Front Side
Recommended enclosure	100.0 dm ³ (3.53 ft ³)
Recommended tuning	50 Hz

Parameters⁴

Fs	42 Hz
Re	5.0 Ω
Qes	0.26
Qms	5.9
Qts	0.25
Vas	164.0 dm ³ (5.8 ft ³)
Sd	855.0 cm ² (132.5 in ²)
η_0	4.5 %
Xmax	5.0 mm
Xvar	8.0 mm
Mms	88 g
Bl	22.1 Txm

Parameters

Le	1.3 mH
EBP	161 Hz

Mounting And Shipping Info

Overall diameter	393 mm (15.5 in)
Bolt circle diameter	374 mm (14.7 in)
Baffle cutout diameter	354.0 mm (13.9 in)
Depth	169 mm (6.65 in)
Flange and gasket thickness	16 mm (0.62 in)
Air volume occupied by driver	5.2 dm ³ (0.18 ft ³)
Net weight	8.5 kg (18.7 lb)
Shipping units	1
Shipping weight	10.2 kg (22.4 lb)
Shipping box	420x420x200 mm (16.5x16.5x7.9 in)

Service Kit


RCK15PLB768

1. 2 hours test made with continuous pink noise signal (6 dB crest factor) within the range Fs-10Fs. Power calculated on rated minimum impedance. Loudspeaker in free air.

2. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

3. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.

4. Thiele-Small parameters are measured after a high level 20 Hz sine wave preconditioning test.



Model: **15 PLB 76**
Enclosure Type: **Bass Reflex**

Internal Net Volume (Liters):	100	Port Area (cm ²):	222.3
Tuning Frequency (Hz):	50	Port Length (cm):	12.0
Frequency (-3 dB) (Hz):	53.5		

Excursion Limited Maximum SPL at 1 meter (dB): **123.1** equal to **312.2** Watts (Bass Band Power Rating)
Thermal Limited Maximum SPL at 1 meter (dB): **124.1** equal to **400.0** Watts (Mid Band Power Rating)