

# 12FE400

12" - 200 W - 97 dB - 8 Ohm



NOMINAL SPECIFICATIONS		TECHNICAL PARAMETERS		THIELE & SMALL PARAMETERS	
Nominal Diameter	300 mm (12 in)	Nominal Impedance	8 Ohm	Fs	55 Hz
Overall Diameter	311 mm (12.24 in)	Minimum Impedance	6 Ohm	Re	5 Ohm
Bolt Circle Diameter	294.5 mm (11.59 in)	AES Power Handling (1)	200 W	Qes	0.63
Baffle Cutout Diameter	284 mm (11.18 in)	Maximum Power Handling (2)	400 W	Qms	6.6
Depth	131 mm (5.16 in)	Sensitivity (1W/1m)	97 dB	Qts	0.57
Flange and Gasket Thickness	7.5 mm (0.30 in)	Frequency Range	55÷4000 Hz	Vas	73.6 dm^3 (2.60 ft^3)
Net Weight	3.1 kg (6.8 lb)	Voice Coil Diameter	44 mm (1.73 in)	Sd	549 cm^2 (85.10 in^2)
Shipping Box (Single Carton Box)	350 x 346 x 190 mm (13.7 x 13.6 x 7.48 in)	Winding Material	Cu	Xmax (4)	5.42 mm
Shipping Weight	3.9 kg (8.6 lb)	Former Material	Al	Xdamage (5)	14.9 mm
		Winding Depth	13.5 mm (0.53 in)	Mms	47.9 g
		Magnetic Gap Depth	8 mm (0.31 in)	Bl	11.5 N/A
		Flux Density	1.10 T	Le	0.75 mH
		Magnet	Ferrite Ring	Mmd	33.4 g
		Basket Material	Steel	Cms	0.17 mm/N
		Demodulation	No	Rms	2.5 kg/s
		Cone Surround (3)	Triple Roll	Eta Zero	1.90 %
		NET Air Volume filled by Loudspeaker	1.9 dm^3 (0.067 ft^3)	EBP	88 Hz
		Spider Profile	1x constant height waves		

- NOTES:**
- (1) 2 Hours Test According to AES 2-1984 Rev. 2003
  - (2) Maximum power is defined as 3dB greater than nominal power.
  - (3) Treated Polycotton
  - (4) Xmax= [(winding depth - magnetic gap depth)/2] + (magnetic gap depth/3)
  - (5) Maximum excursion before permanent damage

