



## DE14

### HF Drivers - 1.0 Inches

60 W continuous program power capacity  
1" horn throat diameter  
36 mm (1.4 in) CCAW voice coil  
Polyester diaphragm  
1500 - 18000 Hz response  
105 dB sensitivity

#### Specifications<sup>1</sup>

Throat diameter	25 mm (1.0 in)
Nominal impedance	8 $\Omega$
Minimum impedance	7.7 $\Omega$
Nominal power handling <sup>2</sup>	30 W
Continuous power handling <sup>3</sup>	60 W
Sensitivity (1W/1m) <sup>4</sup>	105.0 dB
Frequency range	2 - 18 kHz
Recommended crossover <sup>5</sup>	2.2 kHz
Voice coil diameter	36 mm (1.4 in)
Winding material	Aluminium
Inductance	0.14 mH
Diaphragm material	Mylar
Flux density	1.45 T
Magnet material	Ferrite

#### Mounting And Shipping Info

Overall diameter	90 mm (3.5 in)
Depth	49 mm (1.93 in)
Net weight	1.1 kg (2.4 lb)
Shipping units	8
Shipping weight	9.4 kg (20.7 lb)
Shipping box	245x245x185 mm (9.65x9.65x7.3 in)

#### Replacement Diaphragm

MMD0148

#### Mounting And Shipping Info

Two M5 holes 180° on 76 mm (3 in) diameter  
Three M6 holes 120° on 57 mm (2.2 in) diameter

1. Driver mounted on B&C ME 45 horn.
2. 2 hour test made with continuous pink noise signal (6 dB crest factor) within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.
3. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

4. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
5. 12 dB/oct. or higher slope high-pass filter.