



DE95TN

HF Drivers - 2.0 Inches

220 W continuous program power capacity
2" horn throat diameter
75 mm (3 in) CCAW voice coil
Titanium diaphragm
500 - 18000 Hz response
107.5 dB sensitivity
Shorting copper cap for extended HF response

Specifications¹

Throat diameter	50 mm (2.0 in)
Nominal impedance	8 Ω
Minimum impedance	8.3 Ω
Nominal power handling ²	110 W
Continuous power handling ³	220 W
Sensitivity (1W/1m) ⁴	107.5 dB
Frequency range	500 - 18 kHz
Recommended crossover ⁵	1.0 kHz
Voice coil diameter	75 mm (3.0 in)
Winding material	CCAW
Inductance	0.14 mH
Diaphragm material	Titanium
Flux density	1.8 T
Magnet material	Ferrite

Mounting And Shipping Info

Depth	66 mm (2.6 in)
Net weight	4.5 kg (9.9 lb)
Shipping units	2
Shipping weight	9.6 kg (21.2 lb)
Shipping box	210x210x190 mm (8.3x8.3x7.5 in)

Replacement Diaphragm

MMD3DTN8M

Mounting And Shipping Info

Four M6 holes 90° on 102 mm (4 in) diameter	
Overall diameter	170 mm (6.7 in)

1. Driver mounted on B&C ME60 horn
2. 2 hour test made with continuous pink noise signal (6 dB crest factor) within the range from the recommended crossover frequency to 20 kHz. Power calculated on rated minimum impedance.
3. Power on Continuous Program is defined as 3 dB greater than the Nominal rating.

4. Applied RMS Voltage is set to 2.83 V for 8 ohms Nominal Impedance.
5. 12 dB/oct. or higher slope high-pass filter.